

SSF67V SERIES

CONTINUOUS OUTPUT LEVEL TRANSDUCER



This transducer will give an output of 4-20mA over a measuring span of up to 2500mm.

The standard output changes from 4mA at low level to 20mA at high level.

The transducer is top mounting, via a screwed entry, and is normally installed from outside the tank. The device has either a brass or stainless steel stem with either a foamed float or a stainless steel float.

Volt free switches and resistors are mounted in the stem, to provide a varying resistance, as the float rises or falls, which is converted within the device into a 4 to 20mA stepped output.

Features

- 4-20mA transducer for safe area use (optional flameproof certification)
- Maximum process temperature 100°C
- Standard 10mm stepped accuracy
- Standard G1" Screwed entry (G1" to G2.5" possible)

SPECIFICATIONS

Technical

Mounting Style	
Mounting Thread	
Stem Material	
Float Material	
Enclosure Material	
Connection	
Maximum Process Temperature	
Maximum Ambient Temperature	
Minimum Ambient Temperature	

Electrical

Output 4 to 20mA	4mA can be either High or Low
Input Supply	15 to 30Vdc
Can be connected to analogue or digital displays	

STANDARD PARTS

	Upper Level	Measuring Span	Total Length
SSF67V70S500			
SSF67V70S1000			
SSF67V70S1500			

Custom versions can be made for particular applications. Please contact Sensata with your requirements.



Technical drawing of the 1000 Series Cable Mounting Bracket. The drawing includes a side view (labeled VIEW A) and a top view (labeled VIEW A). The side view shows a bracket with a hexagonal base (HEXAGON AF 47mm) and a cable mounting arm. Dimensions include a 70mm (2.75") height, a 15mm (0.6") distance to the Min High Level, a 70mm (2.75") distance to the Max Span, and a 30mm (1.2") distance to the end of the arm. The top view shows a 70mm (2.75") width and a 14mm (0.6") distance to the center of the cable. The cable is labeled G1.0".

Made in the UK

www.sensata.com