



Figure similar

SIMATIC ET 200SP, CM PTP communication module for serial connection RS-422, RS-485 and RS-232, freeport, 3964 (R), USS, MODBUS RTU master, slave, max. 250 Kbit/s, suitable for BU type A0, pack quantity: 1 unit

General information	
Product type designation	CM PtP
Firmware version	
• FW update possible	Yes
usable BaseUnits	BU type A0
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V17 or higher
• STEP 7 configurable/integrated from version	via GSD as of V5.6 HF4
• PROFIBUS from GSD version/GSD revision	GSD as of Revision 5
• PROFINET from GSD version/GSD revision	GSDML V2.34
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	31 mA
Current consumption, max.	35 mA
Power loss	
Power loss, typ.	0.7 W
Address area	
Address space per module	
• Inputs	8 byte; performance mode: 32 byte
• Outputs	0 byte; performance mode: 32 byte
Hardware configuration	
Automatic encoding	Yes
• Mechanical coding element	Yes
• Type of mechanical coding element	type D
1. Interface	
Interface types	
• RS 485	Yes
• RS 422	Yes
• RS 232	Yes
• Design of the connection	Push-in terminal
Interface types	
RS 232	
• Transmission rate, max.	115.2 kbit/s

• Cable length, max.	15 m
• RS 232 auxiliary signals	RTS, CTS, DTR, DSR, RI, DCD
RS 485	
• Transmission rate, max.	250 kbit/s
• Cable length, max.	1 200 m; 100 to 1200 m, depending on transmission speed
RS 422	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	1 200 m
• 4-wire full duplex connection	Yes
• 4-wire multipoint connection	Yes
Protocols	
Integrated protocols	
Freeport	
— Telegram length, max.	2 kbyte; performance mode: receive data max. 24 byte and send data max. 30 byte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
3964 (R)	
— Telegram length, max.	2 kbyte; performance mode: receive data max. 24 byte and send data max. 30 byte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
Modbus RTU master	
— Address area	1 to 247, extended 1 to 65535
— max. number of devices	32
protocols / Modbus RTU device / header	
— Address area	1 to 247, extended 1 to 65535
Telegram buffer	
• Buffer memory for telegrams	4 kbyte
• Number of telegrams which can be buffered	255
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Hardware interrupt	No
Diagnoses	
• Wire-break	Yes
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• for module diagnostics	Yes; green/red DIAG LED
• Receive RxD	Yes; green LED
• Transmit TxD	Yes; green LED
Potential separation	
between backplane bus and interface	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	25.2 kg
— global warming potential, (during production) [CO2 eq]	6.15 kg
— global warming potential, (during operation) [CO2 eq]	19.4 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.289 kg
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C

- horizontal installation, max. - vertical installation, min. - vertical installation, max.	60 °C -30 °C 50 °C																																							
Altitude during operation relating to sea level																																								
Installation altitude above sea level, max.	5 000 m																																							
Decentralized operation																																								
to SIMATIC S7-300	Yes																																							
to SIMATIC S7-400	Yes																																							
to SIMATIC S7-1200	Yes																																							
to SIMATIC S7-1500	Yes																																							
to standard PROFINET controller	Yes																																							
Dimensions																																								
Width	15 mm																																							
Height	73 mm																																							
Depth	58 mm																																							
Weights																																								
Weight, approx.	30 g																																							
Classifications																																								
	<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>14</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>12</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>9</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>8</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>6</td><td>27-24-26-08</td></tr><tr><td>ETIM</td><td>9</td><td>EC001604</td></tr><tr><td>ETIM</td><td>8</td><td>EC001604</td></tr><tr><td>ETIM</td><td>7</td><td>EC001604</td></tr><tr><td>IDEA</td><td>4</td><td>3564</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	14	27-24-26-08	eClass	12	27-24-26-08	eClass	9.1	27-24-26-08	eClass	9	27-24-26-08	eClass	8	27-24-26-08	eClass	7.1	27-24-26-08	eClass	6	27-24-26-08	ETIM	9	EC001604	ETIM	8	EC001604	ETIM	7	EC001604	IDEA	4	3564	UNSPSC	15	32-15-17-05
	Version	Classification																																						
eClass	14	27-24-26-08																																						
eClass	12	27-24-26-08																																						
eClass	9.1	27-24-26-08																																						
eClass	9	27-24-26-08																																						
eClass	8	27-24-26-08																																						
eClass	7.1	27-24-26-08																																						
eClass	6	27-24-26-08																																						
ETIM	9	EC001604																																						
ETIM	8	EC001604																																						
ETIM	7	EC001604																																						
IDEA	4	3564																																						
UNSPSC	15	32-15-17-05																																						
Approvals / Certificates																																								
General Product Approval																																								
Manufacturer Declaration	 EG-Konf. 																																							
Miscellaneous	 UL  RCM																																							
EMV	For use in hazardous locations																																							
KC	 UL CCC-Ex FM																																							
	 ATEX  IECEX																																							
For use in hazardous locations	Marine / Shipping																																							
Miscellaneous	 ABS  BUREAU VERITAS  DNV  LRS																																							
	NK / Nippon Kaiji Kyokai																																							
Marine / Shipping	Environment																																							



[CCS \(China Classification Society\)](#)



last modified:

4/7/2025